



Nominal heating capacity of the Oven	29 Kw
Temperature range of utilization	250/470°C
Flue exit diameter	$\phi 200$ mm.
Flue gas temperature at the manifold	190/270°C
Required extraction Flow	270/290 Nmc/h
$\Delta P$ Flue	- 0,4 mmH <sub>2</sub> O (-3,9Pa)
Electric Power Supply	220/240V - 50Hz - 300W
Gas Pressure Required	Ng- 20 mBar/ Lpg 30 mBar
Required Gas Power	34 Kw
Maximum power of wood's fire	9 Kw



REFRATTARI VALORIANI S.R.L.

Via Caselli alla Fornace 213 -  
50066 Reggello ( FI ) Italia tel. +39-055868069

	NOME	FIRMA	DATA	Aspected Weight
DISEGNATO	Rapaccini A.			<b>Kg 1950</b>
VERIFICATO	Rapaccini A.			
APPROVATO				
QUALITA'				
				FINITURA: <b>Metal = painted graphite Dome = painted white wall</b>

NON SCALARE IL DISEGNO

REVISIONE

TITOLO:

**Rotativo 140  
Dome  
Short Shelf**

N. DISEGNO

**20210311**

A3

SCALA:1:20

FOLGIO 1 DI 1